

Constraint Satisfaction Problems


1

Constraint satisfaction problems (CSPs)

- Standard search problem:
 - state is a “black box”—any old data structure that supports goal test, eval, successor
- CSP:
 - state is defined by variables X_i with values from domain D_i
 - goal test is a set of constraints specifying allowable combinations of values for subsets of variables
- Simple example of a formal representation language
- Allows useful general-purpose algorithms with more power than standard search algorithms

2


Example: Map-Coloring



- Variables WA, NT, Q, NSW, V, SA, T
- Domains $D_i = \{\text{red, green, blue}\}$
- Constraints: adjacent regions must have different colors
 - e.g., $WA \neq NT$ (if the language allows this), or
 - $(WA, NT) \in \{(\text{red, green}), (\text{red, blue}), (\text{green, red}), (\text{green, blue}), \dots\}$

3

Example: Map-Coloring contd.




Solutions are assignments satisfying all constraints, e.g.,
 $\{WA=\text{red}, NT=\text{green}, Q=\text{red}, NSW=\text{green}, V=\text{red}, SA=\text{blue}, T=\text{green}\}$

4

Constraint graph

- **Binary CSP:** each constraint relates at most two variables
- **Constraint graph:** nodes are variables, arcs show constraints
- General-purpose CSP algorithms use the graph structure to speed up search. e.g., Tasmania is an independent subproblem!



5

Varieties of CSPs

- **Discrete variables**
 - finite domains; size $d \Rightarrow O(d^n)$ complete assignments
 - e.g., Boolean CSPs, incl. Boolean satisfiability (NP-complete)
 - infinite domains (integers, strings, etc.)
 - e.g., job scheduling, variables are start/end days for each job
 - need a constraint language, e.g., $StartJob_1 + 5 \leq StartJob_3$
 - linear constraints solvable, nonlinear undecidable
- **Continuous variables**
 - e.g., start/end times for Hubble Telescope observations
 - linear constraints solvable in poly time by LP methods


6

Varieties of constraints

- **Unary constraints** involve a single variable,
 - e.g., $SA \neq green$
- **Binary constraints** involve pairs of variables,
 - e.g., $SA \neq WA$
- **Higher-order constraints** involve 3 or more variables,
 - e.g., cryptarithmic column constraints
- **Preferences (soft constraints),**
 - e.g., red is better than green
 - often representable by a cost for each variable assignment
 - constrained optimization problems

7

Example: Cryptarithmic

$$\begin{array}{r} T W O \\ + T W O \\ \hline F O U R \end{array}$$


- **Variables:** $F T U W R O X_1 X_2 X_3$
- **Domains:** $\{0, 1, 2, 3, 4, 5, 6, 7, 8, 9\}$
- **Constraints**
 - $alldiff(F, T, U, W, R, O)$
 - $O + O = R + 10 \cdot X_1$, etc.

8

Real-world CSPs

- Assignment problems
 - e.g., who teaches what class
- Timetabling problems
 - e.g., which class is offered when and where?
- Hardware configuration
- Spreadsheets
- Transportation scheduling
- Factory scheduling
- Floorplanning
- Notice that many real-world problems involve real-valued variables

9

Standard search formulation (incremental)

- Let's start with the straightforward, dumb approach, then fix it
- States are defined by the values assigned so far
- **Initial state:** the empty assignment, { }
- **Successor function:** assign a value to an unassigned variable that does not conflict with current assignment.
 - fail if no legal assignments (not fixable!)
- **Goal test:** the current assignment is complete
 - 1) This is the same for all CSPs!
 - 2) Every solution appears at depth n with n variables
 - use depth-first search
 - 3) Path is irrelevant, so can also use complete-state formulation
 - 4) $b=(n-l)d$ at depth l , hence $n!d^n$ leaves!!!!

10

Backtracking search

- Variable assignments are commutative, i.e.,
 - [WA=red then NT =green] same as [NT =green then WA=red]
- Only need to consider assignments to a single variable at each node
 - $b=d$ and there are d^n leaves
- Depth-first search for CSPs with single-variable assignments
- is called backtracking search
- Backtracking search is the basic uninformed algorithm for CSPs
- Can solve n-queens for $n \approx 25$

11

Backtracking search

```
function BACKTRACKING-SEARCH(csp) returns solution/failure
  return RECURSIVE-BACKTRACKING({ }, csp)


function RECURSIVE-BACKTRACKING(assignment, csp) returns soln/failure
  if assignment is complete then return assignment
  var ← SELECT-UNASSIGNED-VARIABLE(VARIABLES[csp], assignment, csp)
  for each value in ORDER-DOMAIN-VALUES(var, assignment, csp) do
    if value is consistent with assignment given CONSTRAINTS[csp] then
      add {var = value} to assignment
      result ← RECURSIVE-BACKTRACKING(assignment, csp)
      if result ≠ failure then return result
      remove {var = value} from assignment
  return failure
```

12


Backtracking example




13



14



15



16

Improving Backtracking Efficiency

General-purpose methods can give considerable gains in speed:

1. Which variable should be assigned next?
2. In what order should its values be tried?
3. Can we detect inevitable failure early?
4. Can we take advantage of problem structure?

17

Minimum Remaining Values


- Minimum remaining values (MRV):
 - choose the variable with the fewest legal values



18

Degree Heuristic

- Tie-breaker among MRV variables
- Degree heuristic:
 - choose the variable with the most constraints on remaining variables



19

Least Constraining Value

- Given a variable, choose the least constraining value:
 - The one that rules out the fewest values in the remaining variables



Combining these heuristics makes 1000 queens feasible

20

Forward Checking

- Idea: Keep track of remaining legal values for unassigned variables
- Terminate search when any variable has no legal values



WA	NT	Q	NSW	V	SA	T
<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>

21

Forward Checking

- Idea: Keep track of remaining legal values for unassigned variables
- Terminate search when any variable has no legal values



WA	NT	Q	NSW	V	SA	T
<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>
<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>

22

Forward Checking

- Idea: Keep track of remaining legal values for unassigned variables
- Terminate search when any variable has no legal values



WA	NT	Q	NSW	V	SA	T
<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>
<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>
<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>

23

Forward Checking

- Idea: Keep track of remaining legal values for unassigned variables
- Terminate search when any variable has no legal values




WA	NT	Q	NSW	V	SA	T
<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>
<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>
<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>
<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>	<div><div></div><div></div><div></div></div>

24

Constraint propagation

- Forward checking propagates information from assigned to unassigned variables, but doesn't provide early detection for all failures:



NT and SA cannot both be blue!
Constraint propagation repeatedly enforces constraints locally


25

Arc consistency

- Simplest form of propagation makes each arc consistent

$X \rightarrow Y$ is consistent iff

for every value x of X there is some allowed y




26

Arc consistency

- Simplest form of propagation makes each arc consistent

$X \rightarrow Y$ is consistent iff

for every value x of X there is some allowed y




27

Arc consistency

- Simplest form of propagation makes each arc consistent

$X \rightarrow Y$ is consistent iff

for every value x of X there is some allowed y



If X loses a value, neighbors of X need to be rechecked


28

Arc consistency

- Simplest form of propagation makes each arc consistent

$X \rightarrow Y$ is consistent iff

for every value x of X there is some allowed y



If X loses a value, neighbors of X need to be rechecked

Arc consistency detects failure earlier than forward checking
Can be run as a preprocessor or after each assignment

29

Arc consistency algorithm

```

function AC-3(csp) returns the CSP, possibly with reduced domains
inputs: csp, a binary CSP with variables  $\{X_1, X_2, \dots, X_n\}$ 
local variables: queue, a queue of arcs, initially all the arcs in csp


while queue is not empty do
   $(X_i, X_j) \leftarrow \text{REMOVE-FIRST}(\text{queue})$ 
  if REMOVE-INCONSISTENT-VALUES( $X_i, X_j$ ) then
    for each  $X_k$  in NEIGHBORS[ $X_i$ ] do
      add  $(X_k, X_i)$  to queue

function REMOVE-INCONSISTENT-VALUES( $X_i, X_j$ ) returns true iff succeeds
  removed  $\leftarrow$  false
  for each  $x$  in DOMAIN[ $X_i$ ] do
    if no value  $y$  in DOMAIN[ $X_j$ ] allows  $(x, y)$  to satisfy the constraint  $X_i \leftrightarrow X_j$ 
      then delete  $x$  from DOMAIN[ $X_i$ ]; removed  $\leftarrow$  true
  return removed
    
```

$O(n^2d^3)$, can be reduced to $O(n^2d^2)$ (but detecting all is NP-hard)

30

Problem structure



Tasmania and mainland are independent subproblems
Identifiable as connected components of constraint graph


31

Problem structure (cont.)

- Suppose each subproblem has c variables out of n total
- Worst-case solution cost is $n/c \cdot d^c$, linear in n
- E.g., $n=80, d=2, c=20$
 - $2^{80} = 4$ billion years at 10 million nodes/sec
 - $4 \cdot 2^{20} = 0.4$ seconds at 10 million nodes/sec

32

Tree-structured CSPs




- Theorem: if the constraint graph has no loops, the CSP can be solved in $O(n d^2)$ time
- Compare to general CSPs, where worst-case time is $O(d^n)$
- This property also applies to logical and probabilistic reasoning: an important example of the relation between syntactic restrictions and the complexity of reasoning.

33

Algorithm for tree-structured CSPs


1. Choose a variable as root, order variables from root to leaves such that every node's parent precedes it in the ordering



2. For j from n down to 2, apply $RemoveInconsistent(Parent(X_j), X_j)$
3. For j from 1 to n , assign X_j consistently with $Parent(X_j)$

34

Nearly tree-structured CSPs



- **Conditioning:** instantiate a variable, prune its neighbors' domains
- **Cutset conditioning:** instantiate (in all ways) a set of variables such that the remaining constraint graph is a tree
- Cutset size c
 - runtime $O(d^c \cdot (n - c)d^2)$, very fast for small c

35


Iterative algorithms for CSPs

- Hill-climbing, simulated annealing typically work with "complete" states, i.e., all variables assigned
- To apply to CSPs:
 - allow states with unsatisfied constraints
 - operators reassign variable values
- Variable selection:
 - randomly select any conflicted variable
- Value selection by min-conflicts heuristic:
 - choose value that violates the fewest constraints
 - i.e., hillclimb with $h(n) = \text{total number of violated constraints}$

36

Example: 4-Queens


- **States:** 4 queens in 4 columns ($4^4 = 256$ states)
- **Operators:** move queen in column
- **Goal test:** no attacks
- **Evaluation:** $h(n)$ = number of attacks



37

Performance of min-conflicts

- Given random initial state, can solve n -queens in almost constant time for arbitrary n with high probability (e.g., $n = 10,000,000$)
- The same appears to be true for any randomly-generated CSP except in a narrow range of the ratio
- $R = \text{number of constraints} / \text{number of variables}$



38

Summary

- CSPs are a special kind of problem:
 - states defined by values of a fixed set of variables
 - goal test defined by constraints on variable values
- Backtracking = depth-first search with one variable assigned per node
- Variable ordering and value selection heuristics help significantly
- Forward checking prevents assignments that guarantee later failure
- Constraint propagation (e.g., arc consistency) does additional work to constrain values and detect inconsistencies
- The CSP representation allows analysis of problem structure
- Tree-structured CSPs can be solved in linear time
- Iterative min-conflicts is usually effective in practice

39